Cách Khắc Phục Lỗi Phông Chữ Trong Alarm Display

Bước 1: Tạo 1 file .txt với nội dung bên dưới.



Bước 2: Vào phần mềm Touch Win Pro -> System settings -> Tích chọn Use custom text



Bước 3: Chọn đường dẫn đến file .txt vừa tạo ở Bước 1 -> Open



Bước 4: Tạo Alarm display. Parts -> Alarm -> Alarm display

Project tree Key	e Lookup Do	ownload Onl	ine simulation Offline Simulator Compile System settings Data sampling Alarm record F	Control wind	dow	i ≅ ∓×
Project Industry	A A ₹	↓ + +	今 / 0日20日時間時間時間		(0
- User st Alarm	1111110	200				
Data process				A Kecently	ased	
User fo Operation record	8					
B System Multimedia			9		Light	
B System Torm				Prois and		
Function Block	Ngày tháng T	Thời gian	Y Nội dung	Dasie com	Jouentz	
Header file	3 17/09/2024 2	22:21:36	Alarm Event0	Α	A	012
	2 17/09/2024	22:21:36	Alarm Event1	Static text	t Dynamic text	Value input
= 1	1 17/09/2024	22:21:36	Alarm Event2			
				012	ABC	ABC
8-				Value displa	av Character input	haracter displa
E					,	
				中文	中文	\bigcirc
<u>8-</u>				Chinasa inn	I. I.	Light
1				Chinese mp	at annese display	Light
					0	
-				Laht kau	Aulainaatuu limb	Character have
				v light key	viultistatus lign	character key
Output window			→ #	×	-	
Output Error list						
				Key	Multi state key	Function key
				5-21	321	
				Fn		-

Bước 5: Chọn List Data -> Chọn font chữ hỗ trợ Tiếng Việt (Vd: Arial) -> Ok

Touch Win Pro - Project - [00001]Page1		Alarm display X	- • ×
File Edit Parts Drawing Tool	View Help		
New Open Save OFF Undo Recovery	Copy Cut Paste Delete Lookup Download	Basic Attributes Display Appearance Alarm query Security Location Control ID ADD	it
Project tree 📮 🗶	[00001]Page1*	Description	rol window 🛛 📮 🗙
⊟- 🍙 Project		Alarm source	Q
⊖-⊡ User screen	⊕ º,	Show range 0 \checkmark 254 \checkmark Alarm	ntly used
	-	Use title	\bigcirc
🗈 🗔 System screen	E	Text O Multilan	₩ Light
🗈 🔜 System form	i i i i i i i i i i i i i i i i i i i		Light
E Function Block	- Ngày tháng Thời gian		c components
🔁 Header file	3 17/09/2024 22:27:08		Δ Δ 012
Source file	2 17/09/2024 22:27:08		tis text Demonisteret Value insuit
□ Library	I 17/09/2024 22:27:08		the text Dynamic text value input
		Tabla titla List titla List Data	012 ABC ABC
		For and the carbonal Synchronize language font styles	I I II II
		Col Anal Col General C	display inaracter inpunaracter displa
	E	Alig Middle Center	中文 中文 ()
	- 8-	Now 14	
	E		ise input .ninese display Light
	E		
			nt key Vultistatus lighCharacter key
	Output window		
	Output Error list		
			Key Multi state key Function key
			321
HMI model : TS3-700-M X : 476 Y : 261	Q 🔲	OK Cancel Apply ↓	

Bước 6: Chọn Download -> Tích chọn Download fonts to -> Download

							Download (PC -> HMI)	7			×
File Edit Parts Drawing To	ool \	/iew Help	р					`			
New Open Save OFF Undo Recov	▶	Copy Cut	Paste De	lete	Q Lookup I	Download	Communication settings Connection USB ~	irm record	Recipe Edit		E E
Project tree .	¤ × ∣	[00001]Page	1					-	× Control win	dow	Д р
⊡- 🎓 Project	Te	5 8 8	TT +ff		♠ ₼ ₱	- ↓ →		P.			0
User screen	æ		0			200					~
[00001]Page1							USB Communi		A Recently	ased	
	-						Upload Download				
⊕-🗔 System screen							Downloa •••••				
🗈 🔜 System form	2									Light	
Function Block	-		Ĩ	कार्श्व	Ngày tháng	Thời gian	- Allow project upload		Basic com	ponents	
	=			3	17/09/2024	22:31:32	User defined heat core.		Δ.	~	012
Source file	20			2	17/09/2024	22:31:32			A	HA.	I
i - 🗖 Library	-			1	17/09/2024	22:31:32	-		Static tex	t Dynamic text	Value input
	3								012	ABC	ARC
							Synchronize PC time 🛛 Hide menu system 🗌 Enable installment		I	I	I
	-								Value displa	ay Character inpu	utharacter displa
									ch str		
	-						· ☑ Overwrite recipe data ☑ Download fonts to ☑ Clear PFW/SPFW		ΨX I	I I	\mathbf{Q}
	-								Chinese inp	ut :hinese displa	y Light
	-					-	Please wait, project is compiling				
	-						Please wait, project is compiling				<u> </u>
									✓ light key	Aultistatus lig	hCharacter key
	0	utput window						– ņ	×		Fn
		Output Erro	or list			_			Kev	Multi state ke	ev Function key
	0	Compile windo	w25900 rce file O	uantitvi	71		Download Upload OFF		`		,
	Ċ	Compilation co	ompleted.			_			En	321	
	C	Error, 23Wai	rning, 0Me	essage						Pre Contro	l win 📼 Outlin
HMI model • TS3-700-M X • 286 X • -30	$\oplus \oplus$								Address	Control	
(44										

Bước 7: Như vậy là đã xong. Hãy xem sự khác biệt trên HMI.